

(717) 354-8998 • (877) 560-5966 New Holland, PA

#111 Single Easy Glider



Tools Required

- Hammer
- #2 Square Head Bit
- Power Drill
- 7/16" Socket or 7/16 wrench

Included Hardware

Α	1	6	1/4" x 3" Carriage Bolt
В	<u>)</u>	8	1/4" x 31/2" Carriage Bolt
С		14	1/4" Nut
D		8	¼" x 3" Lag Bolt

Instructions:

- Unpack items from box(es). Be sure to match any numbers & letters that you may find on the pieces.
- 2. To begin, set the seat upright. Set the back into the seat. Align the pre-drilled holes. Fasten the back to the seat using 2 (A) ¼" x 3" Carriage Bolts & 2 (C) ¼" Nuts. (Illustration 2) Repeat on the other side.
- 3. Fasten the arm of the arm/leg combo to the back of the seat using 1 (A) ½" x 3" Carriage Bolt & 1 (C) ½" Nut. Then using 4 (B) ½" x 3½" Carriage Bolts & 4 (C) ½" Nuts fasten the legs to the seat of the glider. (Illustration 3) Repeat on the other side.
- 4. Then install the base rails between the legs. Fasten them using 4 (D) ¼" x 3" Lag Bolts. (Illustration 4) Repeat on the other side.





Illustration 2




Illustration 3



Illustration 4