

EASY CHAIR
ASSEMBLY INSTRUCTIONS



(717) 354-8998 • (877) 560-5966
New Holland, PA





#325 Easy Rocker



Tools Required

- Hammer
- #2 Square Head Bit
- Power Drill
- 7/16" Socket or 7/16 wrench

Included Hardware

A		10	1/4" x 3" Carriage Bolt
B		8	1/4" x 3 1/2" Carriage Bolt
C		18	1/4" Nut
D		2	1/4" x 3" Lag Bolt

Instructions:

1. Unpack items from box(es). Be sure to match any numbers & letters that you may find on the pieces.
2. Set the back into the seat. Align the pre-drilled holes. Using 2 (A) 1/4" x 3" Carriage Bolts and 2 (C) 1/4" Nuts fasten the back to the seat. (Illustration 2) Repeat on the other side.
3. Turn the chair so it is resting on its back and attach the arm and leg combo. Fasten the arm of the arm and leg combo to the back using 1 (A) 1/4" x 3" Carriage Bolt and 1 (C) 1/4" Nut. Then attach the leg to the seat using 2 (B) 1/4" x 3 1/2" Carriage Bolts and 2 (C) 1/4" Nuts. (Illustration 3) Repeat on the other side.
4. Turn the chair upside down so it is resting on its arms. Fasten the two back legs using 2 (B) 1/4" x 3 1/2" Carriage Bolts and 2 (C) 1/4" Nuts. Fasten the small brace to the back using 1 (D) 1/4" x 3" Lag Bolt. (Illustration 4) Repeat on the other side.
5. With the chair still upside down, fasten the rocker runners to the legs. Fasten using 2 (B) 1/4" x 3" Carriage Bolts and 2 (C) 1/4" Nuts. (Illustration 5) Repeat on the other side.



Illustration 2



Illustration 3




Illustration 4




Illustration 5